Fresh Fruit Bunch(FFB) Processing Modification...

by Hermantoro Dkk

Submission date: 27-Mar-2024 08:08AM (UTC+0700)

Submission ID: 2331441428

File name: mantoro_2024_IOP_Conf._Ser.__Earth_Environ._Sci._1297_012084.pdf (745.07K)

Word count: 1797 Character count: 8871

PAPER · OPEN ACCESS

Fresh Fruit Bunch (FFB) Processing Modification to Increase Crude Palm Oil (CPO) Rendement

To cite this article: H Hermantoro et al 2024 IOP Conf. Ser.: Earth Environ. Sci. 1297 012084

View the article online for updates and enhancements.

You may also like

- Retracted: Design and evaluation of ciprofloxacin loaded collagen chitosan oxygenating scaffold for skin tissue engineering
- Satyavrat Tripathi, Bh 4 am Narayan Singh, Singh Divakar et al.
- Composite design bioinspired by the mesocarp of Brazil nut (Bertholletia
- excelsa) M.Sonego, V F Sciuti, R Vargas et al.
- An oxygen-releasing device to improve the survival of mesenchymal stem cells in tissue engineering
 Zuyan Lu, Xia Jiang, Mengqi Chen et al.



Fresh Fruit Bunch (FFB) Processing Modification to Increase Crude Palm Oil (CPO) Rendement


H Hermantoro*, A Ruswanto, S Gunawan and A P Putra

Agricultural Engineering Department, Stiper Agricuture University

*Email: hermantoro@instiperjogja.ac.id

Abstract. Oil palm has grown from an area of 300 thousand ha in 1980 to now 16.1 million ha (according to GAPKI) with CPO production of 40 million tons. People's plantations continue to increase and currently account for 52 percent of the total area of oil palm plantations. In this research, pressing pressure experiments were carried out at 60 bar, 70 bar, and 80 bar, respectively, oil losses in fiber were obtained at 13.22%,9.34%, and 7.63%. Through regression analysis, it was found that oil loss in the mesocarp was 1.1% at a pess pressure of 106 Bar. So from this experiment it can be concluded that separating the mesocarp and kernel before pressing provides an increase in oil yield, minimizing oil loss in fiber. The standard oil loss in fiber is 5% in the current palm oil processing process. After modifying the process, very small oil loss in the fiber can be achieved.

1. Introduction



Palm oil (CPO) is a vegetable oil obtained from the flesh and fiber of the fruit (mesocarp) which contains a lot of oil, mostly from the Elaesis guineensis species. Palm oil is an oil that has high levels of saturated fill including fatty acids esterified with glycerol. During processing, some palm to undergoes oxidation. In the palm oil processing process, the company always strives to optimize the amount of CPO yield. One of the company's management systems that has been established to achieve optimal results is to reduce oil loss in CPO during the production process. Oil loss that occurs at each palm oil processing station is caused by various factors. The high level of oil loss affects the efficiency of the production process, causing losses, this is due to equipment that does not have optimal design capabilities and capacity

Sterilization, fruit stripping, digestion, screw pressing and refining are wet processes in the CPO factory. FFB is sterilized with hot steam. Next, the fruit is crushed using a rotary thresher and continues

to the digester. Fruit that has gone through the digestion process will be pressed with a twinscrew press to extract oil from the FFB. Large particles contained in the oil from the screw press are separated using a vibrating screen. The addition of water to the digester, screw press, and filtering process functions to increase the efficiency of CPO extraction from palm fruit [6]. So far, the stages of the CPO processing process are reception station (weighing and greading), sterilization station (using steam), fruit peeling, digesting and press station and clarification station (clarification). In the actual boiling (sterilization) process in the field there is a continuous syst em sterilizer with a temperature of around 95°C-100°C (pressure around 1-1.5 bar) and a batch system sterilizer with a triple peak temperature of around 135°C-145°C using a pressure of 1.5 - 3.0 bar, time around 80 - 90 minutes, as shown in figure 1.




Figure 1. Flow diagram of the palm oil processing process.

One of the things that can reduce the productivity of palm oil processing is that there is still a large amount of oil or oil content that is still included in the fiber or dregs left over from production. This is caused by the hydraulic cone being less than optimal in applying pressure to the screw, so that the fiber compression process is not optimal. The function of the screw press is to extract the oil (crude oil) in the fruit flesh (mesocarp) as much as possible and break the nuts to a minimum. This tool consists of a cylinder (press cylinder) which has holes and inside it there are two screws (screws) in opposite directions that function as pushing the loose hair towards the cone. The press pressure is regulated by two cones at the end of the press, which can move back and forth hydraulically, so that the screw and cone produce very high pressure in the extraction process. This extraction process must also meet the standard press quality parameters, along with these quality parameters.

6	Table 1. Standard press units.			
No	Parameter	Standard		
1	Oil Losses	< 5%		
2	Broken Nut	<10%		

Based on this background, process modifications need to be carried out, by separating the fiber/mesocarp from the kernel before pressing is carried out on the mesocarp. In this way the cpo can be completely pressed, oil loss through the fiber is close to zero. The aim of the research is:

- 1. change the mesocarp and kernel separation unit before pressing
- 2. Increase CPO yield by increasing mesocarp press pressure so that oil loss is small

1297 (2024) 012084

doi:10.1088/1755-1315/1297/1/012084

2. Materials and methods

This research stage was carried out during the press mach eoperation process, but only changed the Ampere on the control panel with 3 treatments, namely 42-45 Ampere (60 Bar), 43-46 Ampere (70 Bar), and 44-47 Ampere (80 Bar). So by changing the Ampere, the pressure of the hydraulic cone automatically changes according to the rotation of the electric motor. The following is the process or stages of the oil processing process at the palm oil factory and the sampling location, as shown in figure 2.




Figure 2. Palm oil processing flow diagram.

3. Results and discussion

In this research, oil is preferred in the flesh part of the fruit (mesocarp). Meanwhile, the physical condition of nuts or fruit seeds must be considered during the "pressing" process, because after this extraction process the nuts will be reprocessed at the nut and kernel station to extract the kernel, which will later be sold to the kernel oil processing factory or PKO (Palm Kernel Oil). Data on oil losses resulting from the extraction carried out are as follows.

Table 2. Experiment results oil loss in fiber (%).

Treatment	60 Bar	70 Bar	80 Bar
I	9.27	7.98	9.67
II	12.92	9.42	8.37
III	18.69	12.27	7.63
IV	12.01	7.68	8.44
Amount	52.89	37.36	34.13
Average	13.22	9.34	7.63

The regression equation between pressure (bar) and oil loss in fiber is as follows Y = 33655x

1297 (2024) 012084

doi:10.1088/1755-1315/1297/1/012084

1.919, with a coefficient of determination R2 = 0.99. with a coefficient of determination R2 = 0.99. Next, an extrapolation analysis of the equation is carried out so that the smallest oil loss of 1% can be obtained at pressure 220 Bar.




Figure 3. Relationship between pressure and oil loss.

In the design of the flow process palm oil mill the researcher limited the research to the design of the CPO processing process using FFB raw materials with process stages starting from rotary feeder, screw conveyor c/w heater, demesocarper, single screw press, crude oil tank, filter press and storage tank.




Figure 4. Design of the flow process palm oil mill.

IOP Conf. Series: Earth and Environmental Science

1297 (2024) 012084

doi:10.1088/1755-1315/1297/1/012084

4. Conclusions



Through processing modifications, can be designed mill with minimum oil loss in the fibre 1% at pressure of 220 Bar, in other words it can increase oil yield. This research is a preliminary study, to obtain the basis for the mill design, further experiments are still needed.

References

- [1] N. Hairiyah, R. Rizki, and R. A. Wijaya, "Analisis Total Productive Maintenance (Tpm) Pada Stasiun Kernel Crushing Plant (Kcp) Di Pt. X," J. Teknol. Pertan. Andalas, vol. 23, no. 1, p. 103, 2019, doi: 10.25077/jtpa.23.1.103-110.2019.
- [2] Wiyono, "Hasrat menguasai pasar minyak sawit. Info Sawit," 2013, pp. 7(1):12-15.
- [3] GAPKI, "Peran Strategis Sawit Rakyat Indonesia," https://gapki.id/news/3875/peran-strategis-sawit-rakyat-indonesia, p. 13 Februari 2023, 2020.
- [4] "BADAN PUSAT STATISTIK BPS-STATISTICS INDONESIA."
- [5] S. Mangoensoekarjo and H. Semangun, "Manajemen Agrobisnis Kelapa Sawit.," *Gajah Mada Univ. Pr*, 2003.
- [6] A. B. Rantawi, "Korelasi Kadar Air pada Kernel terhadap Mutu Kadar Asam Lemak Bebas Produk Palm Kernel Oil yang Dihasilkan," J. Citra Widya Edukasi, vol. 13, no. 1, pp. 27–32, 2021

Check turnitin 3

ORIGINALITY REPORT

SIMILARITY INDEX

13%

INTERNET SOURCES

PUBLICATIONS

STUDENT PAPERS

PRIMARY SOURCES

M L Khoiruddin, A W Utami, I Irham. "Climate anomaly and palm oil price volatility in Indonesia", IOP Conference Series: Earth and Environmental Science, 2021

Publication

www.eri.u-tokyo.ac.jp

Internet Source

discovery.researcher.life

Internet Source

Submitted to Chattogram Veterinary and **Animal Sciences University**

Student Paper

4

Sakthi Balan Ganapathy, Aravind Raj 5 Sakthivel. "Investigation on the Compressive Characteristics and Optimization of Design Parameters of a Novel Functionally Graded Cell Structure", Functional Composites and Structures, 2024

2%

Publication

7	pubmed.ncbi.nlm.nih.gov Internet Source	1 %
8	Wenny Restikasari, Ruth Eviana Hutabarat, Dyah Wulan Sari, Hendy Cahyono. "Is the Oil Palm Land Efficient in Indonesia?", KnE Social Sciences, 2024 Publication	1%
9	Stella Oyom Bassey, Chiemela Enyinnaya Chinma, Vanessa Chinelo Ezeocha, Olajide Emmanuel Adedeji et al. "Nutritional and physicochemical changes in two varieties of fonio (Digitaria exilis and Digitaria iburua) during germination", Heliyon, 2023 Publication	1%
10	e-journal.unipma.ac.id Internet Source	1 %
11	R M Sari, D M Siagian, Erwin, K Syahputri, I Rizkya, I Siregar. "Affecting factors of CPO yield: An identification", IOP Conference Series: Materials Science and Engineering, 2021	<1%

Exclude quotes On
Exclude bibliography On